

# INSTRA CORPORATION API

Domain Operations

**Version 1.8.5**

March 6th, 2014

## Proprietary Information

This document remains the property of Instra Corporation and may only be used by the recipient for the purpose for which it was sent and shall be returned upon request and/or when no longer needed. The document may not be copied or passed on to third parties without written approval from Instra.

## TABLE of CONTENTS

INSTRAL CORPORATION API .....	1
1. Introduction .....	4
2. Commands .....	5
2.1 Domain Management commands .....	5
2.1.1 CheckDomain .....	5
2.1.2 CreateDomain .....	7
2.1.2 UpdateDomain .....	9
2.1.3 TradeDomain .....	11
2.1.4 TransferDomain .....	12
2.1.5 DeleteDomain .....	14
2.1.6 RenewDomain .....	15
2.1.7 RestoreDomain .....	16
2.1.8 SetDomainAutoRenew .....	17
2.1.9 InfoDomain .....	18
2.1.10 QueryDomainList .....	20
2.1.11 AddDomainWhoisPrivacy .....	23
2.1.12 RemoveDomainWhoisPrivacy .....	25
2.1.13 AddDomainRegistryLock .....	26
2.1.14 RemoveDomainRegistryLock .....	27
2.2 Contact Management commands .....	28
2.2.2 CreateContact .....	28
2.2.3 UpdateContact .....	30
2.2.4 DeleteContact .....	32
2.2.5 InfoContact .....	33
2.2.6 QueryContactList .....	35
2.3 Nameserver Host Management Commands .....	37
2.3.2 AddNameserverHost .....	37
2.3.3 UpdateNameserverHost .....	38
2.3.4 InfoNameserverHost .....	39
2.3.5 CheckNameserverHost .....	40
2.4 Miscellaneous .....	41
2.4.2 QueryTransactionList .....	41
3. API HTTPS Response Codes .....	43
4. Appendix .....	44
Domain Registration Requirements .....	44
▪ .IT Domain Registration .....	44
▪ .COM.SG Domain Registration .....	47
▪ .COM.AU Domain Registration .....	49
▪ .COM.HK Domain Registration .....	52
▪ .HK Domain Registration .....	54
▪ .WEB.ID Domain Registration .....	56
▪ .CO.ID Domain Registration .....	58
▪ .NL Domain Registration .....	59

---

▪ .IE Domain Registration .....	61
▪ .RO Domain Registration.....	63
▪ .COM.TR Domain Registration .....	65
▪ .LV Domain Registration .....	67
▪ .KR Domain Registration .....	69
▪ .COM.PA Domain Registration.....	71
▪ .CO.CR Domain Registration .....	73
▪ .PE Domain Registration .....	75
▪ .EC Domain Registration .....	77
▪ .COM.AR Domain Registration.....	79
▪ .COM.BR Domain Registration.....	81
▪ .COM.MY Domain Registration.....	83
▪ .CA Domain Registration .....	85
▪ .DK Domain Registration.....	87
▪ .FI Domain Registration.....	89
▪ .FR Domain Registration .....	91
▪ .NO Domain Registration .....	93
▪ .RU Domain Registration.....	95

## 1. Introduction

The Instra API was developed to offer our users an easy way to connect to our system to perform domain management operations.

This manual describes commands for:

- Domain API commands.

The manual categorize the commands into the following order:

- Domain management commands
- Contact management commands
- Nameserver management commands

Please note that the Instra API **BASE\_URL** is the entry point to accessing our API. This URL can be obtained by completing the OTE API Access Form which can be downloaded via your online account under the API Documentation link.

## 2. Commands

### 2.1 Domain Management commands

The following commands are used to manage domain names (i.e. create, update, trade, transfer, delete, renew, restore etc.)

#### 2.1.1 CheckDomain

##### Description

CheckDomain is a command that allows you to check the availability of certain domain names.

##### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Description	Value
User	Required	Login ID of the user account	TEXT
Pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>CheckDomain</b>	TEXT
domainN	Required	Name of the domain include extensions. N is number from 1 up to unlimited	TEXT
regionN	Optional	Region value is based on the TLD categories, such as 'ALL', 'GENERIC', 'EUROPE', 'ASIA', 'AMERICA', 'AFRICA'	TEXT ('ALL'   'GENERIC'   'EUROPE'   'ASIA')

##### Returned Properties and Values

Code	Description
200	Command completed successfully
561	One of the parameters was invalid
541	Command failed

Property	Description
DOMAINN	The name of domain with the availability status
COUNTRYN	The country of the domain extension
STATUSN	The availability status of the domain such as "Available", "Not Available", "Taken", "Invalid Namespace"

### Example

1. The following request is to check the availability of domain name “reseller” with various extensions:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=CheckDomain&domain1=reseller1.com&domain2=reseller2.net&domain3=reseller3.de&domain4=reseller4.eu&domain5=reseller5.ae&domain6=reseller6.co.in&domain7=reseller7.co.nl&domain8=reseller8.tv&domain9=reseller.ht&domain10=reseller.cx
```

The response is as follows:

[RESPONSE]

```
code = 200
description = Command completed successfully
DOMAIN1 = reseller1.com
COUNTRY1 = Global
STATUS1 = Available
DOMAIN2 = reseller2.net
COUNTRY2 = Global
STATUS2 = Taken
DOMAIN3 = reseller3.de
COUNTRY3 = Germany
STATUS3 = Available
DOMAIN4 = reseller4.eu
COUNTRY4 = European Union
STATUS 4 = Available
DOMAIN5 = reseller5.ae
COUNTRY5 = United Arab Emirates
STATUS5 = Available
DOMAIN6 = reseller6.co.in
COUNTRY6 = India
STATUS6 = Available
DOMAIN7 = reseller7.co.nl
COUNTRY7 = Netherlands
STATUS7 = Available
DOMAIN8 = reseller8.tv
COUNTRY8 = Tuvalu
STATUS8 = Available
DOMAIN9 = reseller.ht
COUNTRY9 = Haiti
STATUS9 = Taken
DOMAIN10 = reseller.cx
COUNTRY10 = Christmas Island
STATUS10 = Available
```

EOF

## 2.1.2 CreateDomain

### Description

CreateDomain is a command that allows you to register a domain name.

### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>CreateDomain</b>	TEXT
domain	Required	Name of the domain including the extension.	TEXT
period	Required	Registration period: min. 1 year and max. 9 years, according to each registry.	TEXT
registrantcontact	Required	The contact handle ID of Owner/Registrant Contact	TEXT
admincontact	Required	The contact handle ID of Admin Contact	TEXT
techcontact	Required	The contact handle ID of Tech Contact	TEXT
billingcontact	Required	The contact handle ID of Billing Contact	TEXT
nameserverN	Required	Nameserver hostnames with min. 2 and max. 9 nameservers. N is number from 1 to 9.	TEXT
ipaddressN	Optional	The ip address of each nameserver.	TEXT

### Note:

Please check on the appendix for extra requirements on specific TLD extensions.  
(See Appendix page)

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
DOMAINNAME	The name of the domain submitted
DOMAINHANDLEID	The unique id of the domain handle
DOMAINEXPIRYDATE	The registration expiration date

### Example

The following request is to create a domain name “reseller.com”:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=CreateDomain&domain=reseller.com&period=1&registrantcontact=INS-C-12350&admincontact=INS-C-12350&techcontact=INS-C-12350&billingcontact=INS-C-12350&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com
```

The response is as follows:

[RESPONSE]

code = 200

description = Command completed successfully

DOMAINNAME = reseller.com

DOMAINHANDLEID = INS-D-8468

DOMAINEXPIRYDATE = 2009-12-19 05:52:42

EOF



## 2.1.2 UpdateDomain

### Description

UpdateDomain is a command that allows you to update a domain to use different admin, tech and billing contacts. Note that the registrant contact can only be changed via the use of the TradeDomain command.

### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
Pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>UpdateDomain</b>	TEXT
domain	Required	Name of the domain including the extension	TEXT
admincontact	Optional	The contact handle ID of Admin Contact	TEXT
techcontact	Optional	The contact handle ID of Tech Contact	TEXT
billingcontact	Optional	The contact handle ID of Billing Contact	TEXT
nameserverN	Optional	Nameserver hostnames with max. 9 nameserver. N is number from 1 to 9	TEXT
ipaddressN	Optional	The ip address of each nameserver.	TEXT

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
DOMAINNAME	The name of domain submitted
DOMAINUPDATEDDATE	The latest updated date for the domain

### Example

1. The following request is to update the domain contacts for “reseller.com”:

---

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=UpdateDomain&domain=reseller.com&admincontact=INS-C-12349&techcontact=INS-C-12349&billingcontact=INS-C-12349
```

The response is as follows:

```
[RESPONSE]
code = 200
description = Command completed successfully
DOMAINNAME = reseller.com
DOMAINUPDATEDDATE = 2008-12-19 17:58:43
```

EOF

2. The following request is to update the domain nameservers for “reseller.com”:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=UpdateDomain&domain=reseller.com&nameserver1=ns1.instradns.com&nameserver2=ns2.instradns.com
```

The response is as follows:

```
[RESPONSE]

code = 200
description = Command completed successfully
DOMAINUPDATEDDATE = 2008-12-19 18:03:24
```

EOF

### 2.1.3 TradeDomain

#### Description

TradeDomain is a method that allows you to update the registrant/owner contact information of a domain, which is not possible to do via the UpdateDomain method.

#### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
User	Required	Login ID of the user account	TEXT
Pw	Required	Account password	TEXT
Command	Required	Name of command to be executed: <b>TradeDomain</b>	TEXT
Domain	Required	Name of the domain including the extension	TEXT
Registrantcontact	Required	The contact handle ID of the new domain owner	TEXT

#### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
No properties returned	

#### Example

The following request is to change the registrant of the domain name “reseller.com”:

**BASE\_URL?user=reseller.com&pw=resellerapi123&command=TradeDomain&domain=reseller.com&registrantcontact=INS-C-74**

The response is as follows:

**[RESPONSE]**

code = 200

description = Command completed successfully

EOF

## 2.1.4 TransferDomain

### Description

TransferDomains is a method that allows you to transfer a domain that is with a different registrar to Instra.

### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>TransferDomain</b>	TEXT
domain	Required	Name of the domain including the extension	TEXT
period	Required	The renewal period upon the successful transfer. Value is from 0 to 9. If 0 specified means that renewal not included and normally its free.	TEXT
auth	Required	Auth-code info is the domain password, required for some TLDs	TEXT
registrantcontact	Required	The contact handle ID of Owner/Registrant Contact	TEXT
admincontact	Required	The contact handle ID of Admin Contact	TEXT
techcontact	Required	The contact handle ID of Tech Contact	TEXT
billingcontact	Required	The contact handle ID of Billing Contact	TEXT
nameserverN	Optional	Nameserver hostnames with max. 9 nameserver. N is number from 1 to 9	TEXT

---

## Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
No properties returned	

### Example

The following request is to change the registrant of the domain name “reseller.com”:  
BASE\_URL?user=reseller.com&pw=resellerapi123&command=TransferDomain&domain=inst  
raresteller.com&auth=BX5635221&period=1&registrantcontact=INS-C-  
12349&admincontact=INS-C-12349&techcontact=INS-C-12349&billingcontact=INS-C-  
12349&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com

The response is as follows:

[RESPONSE]

code = 200

description = Command completed successfully

EOF

### 2.1.5 DeleteDomain

#### Description

DeleteDomain is a command that allows you to delete a domain.

#### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>DeleteDomain</b>	TEXT
domain	Required	Name of the domain including the extension	TEXT

#### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
No properties returned	

#### Example

The following request is to delete the domain name “reseller.com”:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=DeleteDomain&domain=reseller2.com
```

The response is as follows:

[RESPONSE]

code = 200

description = Command completed successfully

EOF

## 2.1.6 RenewDomain

### Description

RenewDomains is a command that allows you to renew a domain.

### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>RenewDomain</b>	TEXT
domain	Required	Name of the domain including the extension	TEXT
period	Required	Renewal period in years, default = 1	TEXT

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
DOMAINNAME	The name of the domain
DOMAINEXPIRYDATE	The expiry date information of the domain

### Example

The following request is to renew the domain name “reseller.com” depends on the period given in the request:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=RenewDomain&domain=reseller.com&period=1
```

The response is as follows:

```
[RESPONSE]
code = 200
description = Command completed successfully
DOMAINNAME = reseller.com
DOMAINEXPIRYDATE = 2010-12-15
EOF
```

## 2.1.7 RestoreDomain

### Description

RestoreDomain is a command that allows you to re-active a domain that has expired. A late renewal fee is applied when restoring a domain

### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>RestoreDomain</b>	TEXT
domain	Required	Name of the domain including the extension	TEXT
period	Required	Renewal period in years, default = 1	TEXT

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
DOMAINNAME	The name of the domain
DOMAINEXPIRYDATE	The expiry date information of the domain

### Example

The following request is to renew the domain name “reseller.com” depends on the period given in the request:

**BASE\_URL?user=reseller.com&pw=resellerapi123&command=RestoreDomain&domain=reseller.com&period=1**

The response is as follows:

**[RESPONSE]**

code = 200

description = Command completed successfully

DOMAINNAME = reseller.com

DOMAINEXPIRYDATE = 2010-12-15

EOF



## 2.1.8 SetDomainAutoRenew

### Description

SetDomainAutoRenew is a command that allows you to set a domain to have its auto-renew function either enabled or disabled.

### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>SetDomainAutoRenew</b>	TEXT
domain	Required	Name of the domain including the extension	TEXT
renewalmode	Required	Renewal mode is "1" (default) means AUTO-RENEW or "0" means AUTO-DELETE	INTEGER ('0'   '1')

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
No properties returned	

### Example

The following request is to set auto renewal value to "FALSE" for "reseller.com":

**BASE\_URL?user=reseller.com&pw=resellerapi123&command=SetDomainAutoRenew&domain=reseller.com&renewalmode=1**

The response is as follows:

[RESPONSE]  
code = 200  
description = Command completed successfully  
EOF

## 2.1.9 InfoDomain

### Description

InfoDomain is a command that allows you to retrieve details on a particular domain in a user's account.

### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>InfoDomain</b>	TEXT
domain	Required	Name of the domain including the extension	TEXT

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
DOMAINNAME	The name of the domain
CREATEDDATE	The creation date of the domain
UPDATEDDATE	Last updated date of the domain
EXPIRYDATE	The registration expiry date
DOMAINSTATUS	The status of a domain active or not active
DOMAINREQSTATUS	The operation status of a domain
DOMAINHOST	The DNS type of a domain such as FREE_PARKING, DELEGATED, DNS_FORWARDING or REDIRECTION
REGISTRANTCONTACT	The Registrant contact
ADMINCONTACT	The Admin contact
TECHCONTACT	The Technical contact
BILLINGCONTACT	The Billing contact
NAMESERVERN	The nameserver hostname and N is the number from 1 up to 10
IPADDRESSN	The ip address of the nameserver hostname
RENEWALMODE	Information how the domain will be

	renewed
CATEGORY	The category name of a domain
LOCALPRESENCE	This is to determine if the domain registered use a local presence. Value 1 means use local presence or value 0 means no local presence used

### Example

The following request is to get the information related to “reseller.com”:

BASE\_URL?user=reseller.com&pw=resellerapi123&command=InfoDomain&domain=reseller.com

The response is as follows:

[RESPONSE]

```
code = 200
description = Command completed successfully
DOMAINNAME = a173.cz
CREATEDDATE = 2008-12-17 15:57:44
UPDATEDDATE = 2008-12-19 18:57:32
EXPIRYDATE = 2010-12-17 15:57:44
DOMAINREQSTATUS = COMPLETED
DOMAINHOST = Free Parking
REGISTRANTCONTACT = INS-C-12350
ADMINCONTACT = INS-C-12334
TECHCONTACT = INS-C-12334
BILLINGCONTACT = INS-C-12334
NAMESERVER1 = ns1.instradns.com
IPADDRESS1 = 119.252.176.10
RENEWALMODE = AUTO-RENEW
CATEGORY =
LOCALPRESENCE = 0
```

EOF

### 2.1.10 QueryDomainList

#### Description

QueryDomainList is a command that allows you to search through the domains in an account.

#### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>QueryDomainList</b>	TEXT
domain	Optional	Search for: Domain pattern, e.g. .com, ez*.eu, a*star.asia	TEXT
domainhandleridN	Optional	Search by: Domain handler id. N can be replace with number from 1 to unlimited.	TEXT
registrantcontact	Optional	Search by: Registrant Contact	TEXT
admincontact	Optional	Search by: Admin Contact	TEXT
techcontact	Optional	Search by: Tech Contact	TEXT
billingcontact	Optional	Search by: Billing Contact	TEXT
mincreateddate	Optional	Search by: min. domain created date with format (yyyy-mm-dd)	DATETIME
maxcreateddate	Optional	Search by: max. domain created date with format (yyyy-mm-dd)	DATETIME
minupdateddate	Optional	Search by: min. domain updated date with format (yyyy-mm-dd)	DATETIME
maxupdateddate	Optional	Search by: max. domain updated date with format (yyyy-mm-dd)	DATETIME
minexpirydate	Optional	Search by: min. domain expiry date with format (yyyy-mm-dd)	DATETIME
maxexpirydate	Optional	Search by: max. domain expiry date with format (yyyy-mm-dd)	DATETIME
domainstatus	Optional	Search by: domain status with value 1 = ACTIVE or 0 =	INTEGER ('0'   '1')

		NOT ACTIVE	
restorestatus	Optional	Search by: domain restore status with value 1 = Need Restore (it has to be used with domainstatus = 0) or 0 = Not Need Restore	INTEGER ('0'   '1')
categoryid	Optional	The category id of a domain	INTEGER
category	Optional	The category name of a domain	TEXT
orderby	Optional	Sort by: "name, active, created_date, last_update, expiry_date"	TEXT
ordertype	Optional	Sort type is ASC or DESC	TEXT

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
DOMAINN_ID	The id of the domain
DOMAINN_NAME	The name of the domain
DOMAINN_REGISTRANTID	The owner of the domain
DOMAINN_CREATEDDATE	The created date for the domain
DOMAINN_UPDATEDDATE	The last updated date for the domain
DOMAINN_EXPIRYDATE	The expiry date for the domain
DOMAINN_STATUS	The domain status, active or not active
DOMANN_AUTORENEW	The renewal mode on a domain
DOMAINN_CATEGORY	The category name of a domain
TOTAL	The total number of the domain(s) in the list

### Example

1. The following request query a list of domain names which contains the word "reseller" and ".com" at the end:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=QueryDomainList&domain=reseller*.com
```

The response is as follows:

[RESPONSE]

```
DOMAIN1_ID = 8466
DOMAIN1_NAME = reseller.com
DOMAIN1_REGISTRANTID = INS-C-12349
DOMAIN1_CREATEDDATE = 2008-12-19 12:06:01
DOMAIN1_UPDATEDDATE = 2008-12-19 13:23:55
```

DOMAIN1\_EXPIRYDATE = 2009-12-19 12:06:01  
DOMAIN1\_STATUS = ACTIVE  
DOMAIN1\_CATEGORY =

DOMAIN2\_ID = 8467  
DOMAIN2\_NAME = instrareseller.com  
DOMAIN2\_REGISTRANTID = INS-C-12350  
DOMAIN2\_CREATEDDATE = 2008-12-19 17:43:46  
DOMAIN2\_UPDATEDDATE = 2008-12-19 18:33:15  
DOMAIN2\_EXPIRYDATE = 2009-12-19 17:43:46  
DOMAIN2\_STATUS = NO ACTIVE  
DOMAIN2\_CATEGORY =

DOMAIN3\_ID = 8468  
DOMAIN3\_NAME = instrareseller11111.com  
DOMAIN3\_REGISTRANTID = INS-C-12350  
DOMAIN3\_CREATEDDATE = 2008-12-19 17:52:42  
DOMAIN3\_UPDATEDDATE = 2008-12-19 18:33:05  
DOMAIN3\_EXPIRYDATE = 2009-12-19 17:52:42  
DOMAIN3\_STATUS = NO ACTIVE  
DOMAIN3\_CATEGORY =

EOF

2. The following request is to list all domains in your reseller account which sort by expiry:

BASE\_URL?user=reseller.com&pw=resellerapi123&command=QueryDomainList&domain=reseller\*.com&domainstatus=1&orderby=expiry\_date

The response is as follows:

[RESPONSE]

code = 200  
description = Command completed successfully  
DOMAIN1\_ID = 8466  
DOMAIN1\_NAME = reseller.com  
DOMAIN1\_REGISTRANTID = INS-C-12349  
DOMAIN1\_CREATEDDATE = 2008-12-19 12:06:01  
DOMAIN1\_UPDATEDDATE = 2008-12-19 13:23:55  
DOMAIN1\_EXPIRYDATE = 2009-12-19 12:06:01  
DOMAIN1\_STATUS = ACTIVE  
DOMAIN1\_CATEGORY =  
TOTAL = 1

EOF

### 2.1.11 AddDomainWhoisPrivacy

#### Description

AddDomainWhoisPrivacy is a command that allows you to turn on the WHOIS privacy feature of a domain if it is supported.

#### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
Pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>AddDomainWhoisPrivacy</b>	TEXT
domainN	Required	Name of the domain including the extension.	TEXT
periodN	Required	Registration period: min. 1 year and maximum based on the current lifetime of the domain.	TEXT

#### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
DOMAINN_NAME	The name of the domain
DOMAINN_EXPIRYDATE	The expiry date for the domain
DOMAINN_TRANSACTIONID	The domain transaction id for this request
TOTAL	The total number of the domain(s) in the list

#### Example

1. The following request query a list of domain names which contains the word "reseller" and ".com" at the end:

**BASE\_URL?user=reseller.com&pw=resellerapi123&command=AddDomainWhoisPrivacy&domain1=reseller.com&period1=1**

The response is as follows:

**[RESPONSE]**

code = 200  
description = Command completed successfully  
DOMAIN1\_NAME = reseller.com  
DOMAIN1\_EXPIRYDATE = 2010-03-15 00:00:00  
DOMAIN1\_TRANSACTIONID = 731510



## 2.1.12 RemoveDomainWhoisPrivacy

### Description

RemoveDomainWhoisPrivacy is a command that allows you to turn off the WHOIS privacy feature of a domain name.

### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>RemoveDomainWhoisPrivacy</b>	TEXT
domainN	Required	Name of the domain including the extension.	TEXT

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
DOMAINN_NAME	The name of the domain
DOMAINN_EXPIRYDATE	The expiry date for the domain
DOMAINN_TRANSACTIONID	The domain transaction id for this request
TOTAL	The total number of the domain(s) in the list

### Example

1. The following request query a list of domain names which contains the word "reseller" and ".com" at the end:

**BASE\_URL?user=reseller.com&pw=resellerapi123&command=RemoveDomainWhoisPrivacy&domain1=reseller.com**

The response is as follows:

[RESPONSE]  
code = 200  
description = Command completed successfully  
DOMAIN1\_NAME = reseller.com  
DOMAIN1\_EXPIRYDATE = 2010-03-15 00:00:00  
DOMAIN1\_TRANSACTIONID = 749500

### 2.1.13 AddDomainRegistryLock

#### Description

AddDomainRegistryLock is a command that allows you to request a registry lock on a domain name (if supported).

#### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
User	Required	Login ID of the user account	TEXT
Pw	Required	Account password	TEXT
Command	Required	Name of command to be executed: <b>AddDomainRegistryLock</b>	TEXT
domain	Required	Name of the domain including the extension.	TEXT

#### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
DOMAINN_NAME	The name of the domain
DOMAINN_EXPIRYDATE	The expiry date for the domain
DOMAINN_TRANSACTIONID	The domain transaction id for this request
TOTAL	The total number of the domain(s) in the list

#### Example

1. The following request query a list of domain names which contains the word "reseller" and ".com" at the end:

**BASE\_URL?user=reseller.com&pw=resellerapi123&command=AddDomainRegistryLock&domain1=reseller.com**

The response is as follows:

[RESPONSE]

code = 200

description = Command completed successfully

DOMAIN1\_NAME = reseller.com

DOMAIN1\_EXPIRYDATE = 2010-03-15 00:00:00

DOMAIN1\_TRANSACTIONID = 832517

### 2.1.14 RemoveDomainRegistryLock

#### Description

RemoveDomainRegistryLock is a command that allows you to remove a registry lock on a domain name.

#### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>RemoveDomainRegistryLock</b>	TEXT
domainN	Required	Name of the domain including the extension.	TEXT

#### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
DOMAINN_NAME	The name of the domain
DOMAINN_EXPIRYDATE	The expiry date for the domain
DOMAINN_TRANSACTIONID	The domain transaction id for this request
TOTAL	The total number of the domain(s) in the list

#### Example

1. The following request query a list of domain names which contains the word "reseller" and ".com" at the end:

**BASE\_URL?user=reseller.com&pw=resellerapi123&command=RemoveDomainRegistryLock&domain1=reseller.com**

The response is as follows:

[RESPONSE]

code = 200

description = Command completed successfully

DOMAIN1\_NAME = reseller.com

DOMAIN1\_EXPIRYDATE = 2010-03-15 00:00:00

DOMAIN1\_TRANSACTIONID = 857580

## 2.2 Contact Management commands

The following commands are used to check, create, manage and delete contact objects.

### 2.2.2 CreateContact

#### Description

CreateContact is a command that allows you to create a new contact.

#### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>CreateContact</b>	TEXT
title	Optional	Title	TEXT
firstname	Required	First name	TEXT
lastname	Required	Last name	TEXT
org	Optional	Organization	TEXT
street	Required	Street name including street number	TEXT
city	Required	City	TEXT
state	Optional	State / Province	TEXT
zip	Optional	ZIP / Postal Code	TEXT
country	Required	2-letter ISO 3166 Country code	TEXT
phone	Required	Phone number, international syntax	TEXT
fax	Optional	Fax number, international syntax	TEXT
email	Required	Email address	TEXT

#### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
CONTACTHANDLEID	The unique id of contact handle ID

## Example

1. The following request is to create contact for John Smith, which returns the contact handle ID:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=CreateContact&title=Mr&first  
name=John&lastname=Smith&street=38 Franklin St  
&city=Melbourne&state=VIC&zip=3000&country=AU&phone=+61.397483531&email=john.s  
mith@reseller.com
```

The response is as follows:

[RESPONSE]

```
code = 200  
description = Command completed successfully  
CONTACTHANDLEID = INS-C-72
```

EOF

2. The following request is to create contact for Paul Lawrence, which returns the contact handle ID:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=CreateContact&title=Mr&first  
name=Paul&lastname=Lawrence&street=11 Black  
St&city=Chelsea&state=VIC&zip=3196&country=AU&phone=+61.3925534321&email=paul.l  
awrence@reseller.com
```

The response is as follows:

[RESPONSE]

```
code = 200  
description = Command completed successfully  
CONTACTHANDLEID = INS-C-74
```

EOF

## 2.2.3 UpdateContact

### Description

UpdateContact is a command that allows you to modify an existing contact.

### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>UpdateContact</b>	TEXT
contacthandleid	Required	The contact handle ID that will be modified	TEXT
title	Optional	Title	TEXT
firstname	Optional	First name	TEXT
lastname	Optional	Last name	TEXT
org	Optional	Organization	TEXT
street	Optional	Street name including street number	TEXT
city	Optional	City	TEXT
state	Optional	State / Province	TEXT
zip	Optional	ZIP / Postal Code	TEXT
country	Optional	2-letter ISO 3166 Country code	TEXT
phone	Optional	Phone number, international syntax	TEXT
fax	Optional	Fax number, international syntax	TEXT
email	Optional	Email address	TEXT

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
No properties returned	

**Note:** Using the UpdateContact function to update a contact's firstname, lastname, company or email is prohibited if the contact is a registrant contact and currently associated with one or more domain names.

## Example

The following request is to update the detail of an existing contact for John Smith using the contact handle ID:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=UpdateContact&contactID=INS-C-72&firstname=John&lastname=Smith&street=38 Lonsdale St&city=Melbourne&state=VIC&zip=3000&country=AU&phone=+61.397721125&email=john.smith@reseller.com
```

The response is as follows:

[RESPONSE]

code = 200

description = Command completed successfully

CONTACTHANDLEID = INS-C-72

EOF

## 2.2.4 DeleteContact

### Description

DeleteContact is a command that allows you to delete a contact.

### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>DeleteContact</b>	TEXT
contacthandleid	Required	Handle ID of the contact	INTEGER

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
No properties returned	

**Note:** Using theDeleteContact function to delete a contact is prohibited if the contact is currently associated with one or more domain names.

### Example

The following request is to delete an existing contact based on the contact handle ID given:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=DeleteContact&contactid=INS-C-73
```

The response is as follows:

```
[RESPONSE]
```

```
code = 200
```

```
description = Command completed successfully
```

```
EOF
```



## 2.2.5 InfoContact

### Description

InfoContact is a command that allows you to retrieve details of an existing contact.

### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>InfoContact</b>	TEXT
contacthandleid	Optional	Handle ID of the contact	INTEGER

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
CONTACTHANDLEID	The handle ID for the contact
FIRSTNAME	The first name of the contact
LASTNAME	The last name of the contact
COMPANY	The company detail of the contact
ADDRESS	The address detail of the contact
CITY	The city of the contact
STATE	The state of the contact
POSTCODE	The postcode of the contact
COUNTRY	The country of the contact
PHONE	The phone number of the contact
FAX	The fax number of the contact
EMAIL	The email information of the contact

### Example

The following request is to get the information of a contact:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=InfoContact&contactid=INS-C-72
```

The response is as follows:

[RESPONSE]

```
code = 200
description = Command completed successfully
CONTACTHANDLEID = INS-C-72
FIRSTNAME = John
LASTNAME = Smith
COMPANY = NULL
ADDRESS = Lonsdale St
CITY = Melbourne
STATE = VIC
POSTCODE = 3000
COUNTRY = AU
PHONE = +61.397483531
FAX = NULL
EMAIL = john.smith@reseller.com
```

EOF

## 2.2.6 QueryContactList

### Description

QueryContactList is a command that allows you to search through the contacts in an account.

### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>QueryContactList</b>	TEXT
contacthandleid	Optional	Search by: Registrant Contact handle ID	INTEGER
firstname	Optional	The first name of any contact	TEXT
lastname	Optional	The last name of any contact	TEXT
org	Optional	The organization name of any contact	TEXT
street	Optional	Street name	TEXT
city	Optional	City	TEXT
state	Optional	State / Province	TEXT
postcode	Optional	ZIP / Postal Code	TEXT
countrycode	Optional	2-letter ISO 3166 Country code	TEXT
phone	Optional	Phone number, international syntax	TEXT
fax	Optional	Fax number, international syntax	TEXT
email	Optional	Email address	TEXT
orderby	Optional	Sort by: "firstname, lastname, email"	TEXT
ordertype	Optional	Sort type is ASC or DESC	TEXT
contentsearch	Optional	To search the content by firstname, lastname, organization or email.	TEXT

### Returned Properties and Values

Code	Description
200	Command completed successfully

---

541	The command failed
-----	--------------------

Property	Description
CONTACTN_HANDLEID	The id of the contact
CONTACTN_FIRSTNAME	The first name of a contact
CONTACTN_LASTNAME	The last name of a contact
CONTACTN_ORG	The organization of a contact
CONTACTN_EMAIL	The email of a contact
TOTAL	The total number of the contact(s) in the list

## 2.3 Nameserver Host Management Commands

The following commands are used to check, create, manage and delete nameserver objects.

### 2.3.2 AddNameserverHost

#### Description

AddNameserverHost is a command that allows you to create a new nameserver host entry to be able to delegate domains to.

#### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Description	Value
User	Required	Login ID of the user account	TEXT
Pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>AddNameserverHost</b>	TEXT
nameserver	Required	Name of the nameserver host	TEXT
ipaddressN	Optional	The ip address of a nameserver host.	TEXT

#### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
No properties returned	

#### Example

The following request is to add a nameserver host of your own domain:

```
BASE_URL?user=reseller.com&pw=resellerapi123&command=AddNameserverHost&nameserver=ns1.resellerdns.com&ipaddress1=102.21.119.35&ipaddress2=102.21.119.34
```

The response is as follows:

```
[RESPONSE]
code = 200
description = Command completed successfully
EOF
```

### 2.3.3 UpdateNameserverHost

#### Description

UpdateNameserverHost is a command that allows you to change the set IP address of a nameserver entry that was created using the CreateNameserverHost command.

#### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>UpdateNameserverHost</b>	TEXT
nameserver	Required	Name of the nameserver host	TEXT
ipaddressN	Required	The ip address of the nameserver host.	TEXT

#### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
No properties returned	

#### Example

The following request is to update an existing nameserver host:

**BASE\_URL?user=reseller.com&pw=resellerapi123&command=UpdateNameserverHost&nameserver=ns1.resellerdns.com&ipaddress1=112.23.79.52**

The response is as follows:

**[RESPONSE]**

code = 200

description = Command completed successfully

**EOF**

## 2.3.4 InfoNameserverHost

### Description

InfoNameserverHost is a command that allows you retrieve the details of a nameserver entry that was created using the CreateNameserverHost command.

### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>InfoNameserverHost</b>	TEXT
nameserver	Required	Name of the nameserver host	TEXT

### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
NAMESERVERHOST	Name of the nameserver host
IPADDRESS	The ip address of the nameserver host.

### Example

The following request is to info an existing nameserver host:

**BASE\_URL?user=reseller.com&pw=resellerapi123&command=InfoNameserverHost&nameserver=ns1.resellerdns.com**

The response is as follows:

**[RESPONSE]**

code = 200

description = Command completed successfully

NAMESERVERHOST = ns1.resellerdns.com

IPADDRESS = 202.118.212.113

EOF

### 2.3.5 CheckNameserverHost

#### Description

CheckNameserverHost is a command that allows you check the existence of nameserver host entries in our system.

#### Input Parameters

Submit the request using the following syntax:

**BASE\_URL?user=username&pw=password&command=commandName&parameter1=value1&parameter2=value2&parameter3=value3...**

Parameter	Obligation	Description	Value
User	Required	Login ID of the user account	TEXT
Pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>CheckNameserverHost</b>	TEXT
nameserverN	Required	Name of the nameserver host	TEXT

#### Returned Properties and Values

Code	Description
200	Command completed successfully
541	The command failed

Property	Description
NAMESERVERHOSTN	Name of the nameserver host
NAMESERVERHOSTN_STATUS	The status of nameserver with value "1" means exist or value "0" means not exist

#### Example

The following request is to check a nameserver host:

**BASE\_URL?user=reseller.com&pw=resellerapi123&command=CheckNameserverHost&nameserver1=ns1.resellerdns.com**

The response is as follows:

**[RESPONSE]**

code = 200

description = Command completed successfully

NAMESERVERHOST1 = ns1.resellerdns.com

NAMESERVERHOST1\_STATUS = 1

**EOF**



## 2.4 Miscellaneous

The following are additional API commands that have been implemented for added functionality.

### 2.4.2 QueryTransactionList

#### Description

QueryTransactionList is a command that allows you to search through the transactions of a user account.

#### Input Parameters

Submit the request using the following syntax:

```
BASE_URL?user=reseller.com&pw=secret&command=commandName&parameter1=value1
&parameter2=value2&parameter3=value3...
```

Parameter	Obligation	Definition	Value
user	Required	Login ID of the user account	TEXT
pw	Required	Account password	TEXT
command	Required	Name of command to be executed: <b>QueryTransactionList</b>	TEXT
product	Optional	Search for: Domain pattern, e.g. .com, ez*.eu, a*star.asia	DOMAIN
producttype	Optional	The type of the product such as 'DOMAIN', 'PHNUM', 'HOSTING'	TEXT
mincreateddate	Optional	Search by: min. created date with format (yyyy-mm-dd)	DATETIME
maxcreateddate	Optional	Search by: max. created date with format (yyyy-mm-dd)	DATETIME
minupdateddate	Optional	Search by: min. updated date with format (yyyy-mm-dd)	DATETIME
maxupdateddate	Optional	Search by: max. updated date with format (yyyy-mm-dd)	DATETIME
operationtype	Optional	The operation of a domain e.g. CREATE, UPDATE, RENEW, TRANSFER	TEXT
referencetype	Optional	This the reference type such as DOMAIN, PHNUM, CONTACT or NAMESERVER	TEXT
productreqstatusN	Optional	Search by: domain operation status such as PENDING, IN_PROGRESS, COMPLETED, FAILED, CREDIT	TEXT

transationidN	Optional	Search by transaction id	TEXT
orderby	Optional	Sort by: "name, active, req_status, created_date, last_update, expiry_date"	TEXT
ordertype	Optional	Sort type is ASC or DESC	TEXT

**Note: Unless specified otherwise all records in the past 3 months will be retrieved.**

#### Returned Properties and Values

Code	Description
200	Command completed successfully
561	One of the parameters was invalid
541	Command failed

Property	Description
TRANSACTIONN_ID	The transaction id of a domain
TRANSACTIONN_NAME	This is the product name such as domain or phnum
TRANSACTIONN_TYPE	This is the type of transaction e.g. CREATE DOMAIN or CREATE PHNUM
TRANSACTIONN_STATUS	This is the status of transaction
TRANSACTIONN_DESCRIPTION	This is the detail information of the transaction from the registry response
TRANSACTIONN_CREATED	This is the date of transaction created
TRANSACTIONN_UPDATED	This is the updated date of the transaction
TRANSACTIONN_USER	This is the user who creates the transaction
TOTAL	The total number of the list

### 3. API HTTPS Response Codes

Status code responses:

Code	Description
200	<b>"Command completed successfully"</b>
521	<b>"Authorization failed"</b>
541	<b>"Command failed" or "Exception Error"</b>
542	<b>"Unknown command"</b>
561	<b>"One of the parameter is invalid"</b>
564	<b>"Required parameter is missing"</b>
581	<b>"Insufficient credit"</b>

## 4. Appendix

### Domain Registration Requirements

There are particular requirements/restrictions that apply for the registration of specific Country Code Top Level Domains (ccTLDs).

Here is the list of requirements for those ccTLDs and the parameters that need to be passed to the “CreateDomain” API command upon registration (when applicable).

#### ▪ **.IT Domain Registration**

##### Restrictions

1. Only individual or company residing in or belonging to a EU Member state can register .it domain names.
2. Nameservers for an .IT domain have to be correctly configured before the actual registration, else the registration will fail.  
Please check the following requirements are met:
  - The master server stated in the SOA of the zone must be one the nameservers given with the domain application.
  - Each nameserver stated in the application must have a valid NS entry.

##### Special Input Parameters

To register .it domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **it-local-presence (Instra Local Presence Service)**

This is our local presence service to register .it domain.

If you set the value of “it-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in European Union member state to register .it domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .it domain:

##### For Company,

#### ➤ **it-doc-number (VAT Number)**

This is the VAT number of a company, which is located within European Union members.

#### ➤ **it-reg-country (Country of Incorporation)**

This is the name of country where the company is incorporated.

#### ➤ **it-reg-type (The type of registrant)**

The accepted value for this parameter is one of the numbers below. Each number represents a type of registrant as follow:

- 1 = Italian and foreign natural persons
- 2 = Companies or one man companies
- 3 = Freelance workers or professionals
- 4 = Non-profit organisations
- 5 = Public organisations
- 6 = Other subjects
- 7 = Foreign organisations

**For Individual,**

- **it-doc-number (Passport No / Taxpayer Code)**  
This is the taxpayer code or passport number of the individual person as the registrant.
- **it-reg-country (Country of Birth)**  
This is the country of birth of the individual person as the registrant.
- **it-reg-type (The type of registrant)**  
The accepted value for this parameter is one of the numbers below. Each number represents a type of registrant as follow:
  - 1 = Italian and foreign natural persons
  - 2 = Companies or one man companies
  - 3 = Freelance workers or professionals
  - 4 = Non-profit organisations
  - 5 = Public organisations
  - 6 = Other subjects
  - 7 = Foreign organisations

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
it-local-presence	Required	Value is '0' or '1'. Set this parameter to 1, if you require us to provide a local presence in registering the domain.	TEXT ('0'   '1')
<b>For a Company, if it-local-presence is set to 0 then details below required:</b>			
it-doc-number	Required	VAT of a company MUST be located within European Union members	TEXT
it-reg-country	Required	The name of country where the company is incorporated	TEXT
it-reg-type	Required	The type of registrant. Value is based on numbers given above.	TEXT
<b>For an Individual, if it-local-presence is set to 0 then details below required:</b>			
it-doc-number	Required	Taxpayer code or passport number of a person as a registrant	TEXT

it-reg-country	Required	Country of birth of a person as a registrant	TEXT
it-reg-type	Required	The type of registrant. Value is based on numbers given above.	TEXT

### Example

1. The following request is to add a domain “reseller.it” with local presence provided:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.it&period=1&registrantContact=INS-C-76&adminContact=INS-C-76&techContact=INS-C-76&billingContact=INS-C-76&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&it-local-presence=1
```

2. The following request is to add a domain “reseller.it” with NO local presence provided:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.it&period=1&registrantContact=INS-C-72&adminContact=INS-C-72&techContact=INS-C-72&billingContact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&it-local-presence=0&it-doc-number=ZN94837392&it-reg-country=United Kingdom&it-reg-type=7
```

## ▪ **.COM.SG Domain Registration**

### **Restrictions**

1. .COM.SG domains are only available for organizations located in Singapore.
2. RCBID number given must be registered with ACRA (is a government body who manage all company registration number located in Singapore)
3. There is a maximum number of 3 nameservers allowed.

### **Special Input Parameters**

To register .com.sg domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **comsg-local-presence (Instra Local Presence Service)**

This is our local presence service to register .com.sg domain.

If you set the value of “comsg-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Singapore to register com.sg domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .com.sg domain:

### **For company only:**

#### ➤ **comsg-doc-number (Business Registration Number)**

This is the Business Registration Number (RCBID) of a company.

#### ➤ **Comsg-singpass-id (Admin contact SingPass ID)**

This is the Business Registration Number (RCBID) of a company.

### **Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
comsg-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)
<b>If comsg-local-presence is set to 0 then details below required:</b>			
comsg-doc-number	Required	Companies located in Singapore must enter their business registration number (RCBID)	TEXT
comsg-singpass-id	Required	Admin contact SingPass ID located in Singapore	TEXT

### Example

1. The following request is to add a domain “reseller.com.sg” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.sg&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&comsg-local-presence=1
```

2. The following request is to add a domain “reseller.com.sg” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.sg&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&comsg-local-presence=0&comsg-doc-number=TM4329873
```



## ▪ **.COM.AU Domain Registration**

### **Note:**

- 1) This condition below also applies to **.NET.AU**, **.ORG.AU**, **.ASN.AU**, and **.ID.AU** domain registration as well.
- 2) All prefix “comau” for the special parameters is replaced with “netau”, “orgau”, “ansau”, “idau”.
- 3) Instra local presence service is not available for all .au domain registrations.

### **Restriction**

1. Only companies and individual located in Australia can register .com.au domain names.
2. Fixed registration of 2 years

### **Special Input Parameters**

To register .com.au domain, the corresponding special information is required to complete the domain registration:

#### ➤ **comau-eligibility-type**

This is the type of the registrant. The available options are:

- Company
- Registered Business
- Sole Trader
- Partnership
- Trademark Owner
- Pending TM Owner
- Citizen/Resident
- Incorporated Association
- Unincorporated Association
- Club
- Non-profit Organisation
- Charity
- Trade Union
- Industry Body
- Commercial Statutory Body
- Political Party
- Religious/Church Groups
- Other

#### ➤ **comau-reg-name (Business Name/Sole Trader Name)**

This is the registrant’s business name which is registered in Australia.

#### ➤ **comau-doc-type (Document Type)**

This is the type of the documents provided based on the registrant eligibility type selected. The available options are:

- ABN for Australian Business Number

- ACN for Australian Company Number
- ACT BN for ACT Business Number
- NSW BN for NSW Business Number
- NT BN for NT Business Number
- QLD BN for QLD Business Number
- SA BN for SA Business Number
- TAS BN for TAS Business Number
- VIC BN for VIC Business Number
- WA BN for WA Business Number
- TM Number for Australian Trademark Number
- OTHER for Other Business or Trademark Number

➤ **comau-doc-number (Document Number)**

This is the document number based on the document type provided from above.

➤ **comau-policy-reason (Policy Reason)**

This is to determine if the domain you are registering is an exact match or a close match to the registrant name, options are:

- 1 for an exact match
- 2 for a close match

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
comau-eligibility-type	Required	This is the type of registrant with possible values mentioned above.	TEXT
comau-reg-name	Required	This is the registrant's business entity name	TEXT
comau-doc-type	Required	This is the type of document, with possible values: ABN   ACN   OTHER	TEXT
comau-doc-number	Required	This is the document number based on the document type provided	TEXT
comau-policy-reason	Required	This value is 1 or 2 based on the purpose of use of this domain. Set value to 1 if the domain you are registering is an exact match to your company name, else set to value 2.	TEXT

---

### Example

The following request is to add a domain “reseller.com.au” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.au&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&comau-local-presence=0&comau-eligibility-type=Company&comau-reg-name=Reseller Corporation Pty Ltd&comau-doc-type=ABN&comau-doc-number=87652462TU&comau-policy-reason=2
```

## ▪ **.COM.HK Domain Registration**

### **Restrictions**

1. .COM.HK domains are only available for organizations located in Hong Kong.
2. Fixed registration of 1, 2, 3 and 5 years

### **Special Input Parameters**

To register .com.hk domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **comhk-local-presence (Instra Local Presence Service)**

This is our local presence service to register .com.hk domain.

If you set the value of “comhk-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Hong Kong to register .com.hk domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .com.hk domain:

#### ➤ **comhk-doc-type (Document Type)**

This is the type of document required to register the domain. The available options are:

- BR = Business Registration Certificate
- CI = Certificate of Incorporation
- CRS = Certificate of Registration of a School
- HKSARG = Hong Kong Special ARG
- HKORDINANCE = Ordinance of Hong Kong

#### ➤ **comhk-doc-number (Document Number)**

This is the document number based on the document type provided from above.

#### ➤ **comhk-doc-origin (Document Origin)**

This is the name of country in 2-letter country code based on ISO 3166 where the document is issued.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
localpresence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	INTEGER (‘0’   ‘1’)

**if comhk-local-presence is set to 0 then parameters below required:**

comhk-doc-type	Required	Document type must be provided based on the registrant as a company, values are: BR CI CRS HKSARG HKORDINANCE	TEXT
comhk-doc-number	Required	Document number based on the document type must be provided.	TEXT
comhk-doc-origin	Required	Country origin of the document. Value is 2-letter ISO 3166 Country code	TEXT

**Example**

1. The following request is to add a domain “reseller.com.hk” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.hk&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&comhk-local-presence=1
```

2. The following request is to add a domain “reseller.com.hk” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.hk&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver0=ns1.resellerdns.com&nameserver1=ns2.resellerdns.com&comhk-local-presence=0&comhk-doc-type=BR&comhk-doc-number=B2982921&comhk-doc-origin=HK
```

## ▪ **.HK Domain Registration**

### **Restrictions**

1. .HK domains are available for organizations and individual.
2. Fixed registration of 1, 2, 3 and 5 years

### **Special Input Parameters**

To register .hk, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **hk-local-presence (Instra Local Presence Service)**

This is our local presence service to register .hk domain.

If you set the value of “hk-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Hong Kong to register .hk domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .hk domain:

#### ➤ **hk-doc-type (Document Type)**

This is the type of document required to register the domain. The available options are:

- HKID = Hong Kong Identity
- OTHID = Other’s Country Identity
- PASSID = Hong Kong Passport Number
- BIRTHCERT = Birth Certificate

#### ➤ **hk-doc-number (Document Number)**

This is the document number based on the document type provided from above.

#### ➤ **hk-doc-origin (Document Origin)**

This is the name of country in 2-letter country code based on ISO 3166 where the document is issued.

#### ➤ **hk-dob (Date of Birth)**

This is the date of birth of the registrant.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
hk-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local	INTEGER (‘0’   ‘1’)

		presence in registering the domain.	
<b>if hk-local-presence is set to 0 then parameters below required:</b>			
hk-doc-type	Required	Document type must be provided based on the registrant as an individual, values are: HKID OTHID PASSID BIRTHCERT	TEXT
hk-doc-number	Required	Document number based on the document type must be provided.	TEXT
hk-doc-origin	Required	Country origin of the document. Value is 2-letter ISO 3166 Country code	TEXT
hk-dob	Required	Date of birth of the registrant in YYYY-MM-DD format	DATETIME

### Example

1. The following request is to add a domain “reseller.hk” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.hk&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&hk-local-presence=1
```

2. The following request is to add a domain “reseller.hk” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.hk&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&hk-local-presence=0&hk-doc-type=HKID&hk-doc-number=BDW289234&hk-doc-origin=HK&hk-dob=1988-06-11
```

## ▪ **.WEB.ID Domain Registration**

### **Restrictions**

1. Only available for individual located in Indonesia.
2. Required to have proof of document such as KTP (Indonesian National ID) or SIM (Indonesian Driver License)

### **Special Input Parameters**

To register .web.id, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **webid-local-presence (Instra Local Presence Service)**

This is our local presence service to register .web.id domain.

If you set the value of “webid-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Indonesia to register .web.id domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .web.id domain:

#### ➤ **webid-doc-type (Document Type)**

This is the type of document required to register the domain. The available options are:

- KTP = Indonesian National ID
- SIM = Indonesian Driver License

#### ➤ **webid-doc-number (Document Number)**

This is the document number based on the document type provided from above.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
webid-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	INTEGER (‘0’   ‘1’)
<b>if webid-local-presence is set to 0 then parameters below required:</b>			
webid-doc-type	Required	Document type must be provided based on the registrant as an individual, values are: KTP or SIM	TEXT
webid-doc-	Required	Document number based on	TEXT



number		the document type must be provided.	
--------	--	-------------------------------------	--

### Example

1. The following request is to add a domain “reseller.web.id” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.web.id&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&webid-local-presence=1
```

2. The following request is to add a domain “reseller.web.id” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.web.id&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&webid-local-presence=0&webid-doc-type=SIM&webid-doc-number=89237419851
```

## ▪ **.CO.ID Domain Registration**

### **Note:**

Instra local presence service is not available for .co.id domain.

### **Restrictions**

1. Only available for company registered and located in Indonesia.
2. Required to have the proof of documents for KTP (Indonesian National ID), SIUP (Business Registration Certificate) and NPWP (Taxation Certificate)

### **Special Input Parameters**

To register .co.id, the corresponding special information is required to complete the domain registration:

- **coid-id-number (Identification Document)**  
This is the registrant's identification document number such as KTP (Indonesian National ID) or SIM (Indonesian Driver License) or Indonesian Passport.
- **coid-siup-number (Business Registration Certificate)**  
This is the business registration certificate number of the registrant as a company.
- **coid-npwp-number (Taxation Certificate)**  
This is the taxation certificate number of the registrant as a company.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
coid-id-number	Required	Identification document number of the registrant	TEXT
coid-siup-number	Required	Business Registration Certificate number of the registrant	TEXT
coid-npwp-number	Required	Company Taxation certificate of the registrant	TEXT

### **Example**

1. The following request is to add a domain "reseller.co.id" with NO local presence:  
 BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.co.id  
 &period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-  
 72&billingcontact=INS-C-  
 72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&coid-local-  
 presence=0&coid-id-number=27018403222&coid-siup-number=3823301985&coid-npwp-  
 number=992140293722332

## ▪ **.NL Domain Registration**

### **Restrictions**

1. Only available to company and individual which are located in the Netherlands.
2. If registrant is a company, Legal Form type and Legal Registration Number are required
3. If registrant is an individual, as long as the registrant's address is located in Netherlands.

### **Special Input Parameters**

To register .nl, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **nl-local-presence (Instra Local Presence Service)**

This is our local presence service to register .nl domain.

If you set the value of "nl-local-presence" parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Netherlands to register .nl domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent's detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .nl domain:

#### ➤ **nl-reg-type (Registrant Legal Type)**

This is the type of legal form of the registrant. The available options are:

- BVI/O = Private Company being Established
- BV = Private Company
- BEG = Foreign EC Company
- BRO = Foreign Law Firm/Enterprise/Subsidiary
- CV = Limited Partnership
- COOP = Cooperation
- EENMANSZAAK = One-man Enterprise
- EESV = European Economical Community (EEC)
- KERK = Religious Society
- NV = Limited Liability Company
- OWM = Mutual Warrant Company
- REDR = Shipping Company
- STICHTING = Foundation
- VOF = Company under Firm
- VERENIGING = Society
- ANDERS = Other

#### ➤ **nl-doc-number (Legal Registration Number)**

This is the legal registration number based on the type of legal form given.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
nl-local-presence	Required	Value is '0' or '1'. Set this parameter to "1", if you require us to provide a local presence in registering the domain.	INTEGER ('0'   '1')
<b>if nl-local-presence is set to 0 then parameters below required:</b>			
nl-reg-type	Required	The type of legal form of the registrant	TEXT
nl-doc-number	Required	The legal registration number based on the legal type provided by the registrant	TEXT

### Example

1. The following request is to add a domain "reseller.nl" with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.nl&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&nl-local-presence=1
```

2. The following request is to add a domain "reseller.nl" with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.nl&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&nl-local-presence=0&nl-reg-type=Other&nl-doc-number=398175191134
```

## ▪ **.IE Domain Registration**

### **Note:**

Instra local presence service is not available for .ie domain.

### **Restrictions**

1. Only available for company registered and located in Ireland and also individual located in Ireland.
2. Fixed 1 year registration.

### **Special Input Parameters**

To register .ie, the corresponding special information is required to complete the domain registration:

#### **For Company,**

- **ie-reg-cof (Country of Company Formation)**  
This is the country name of company formation in the 2-letter country code.
- **ie-doc-number (Company Registration Number)**  
This is the company registration number.

#### **For Trademark,**

- **ie-reg-name (Registered Trademark Name)**  
This is the registered trademark name in Ireland.
- **ie-doc-number (Registered Trademark Number)**  
This is the registered trademark number.
- **ie-doc-origin (Country of Registered Trademark)**  
This is the country where the trademark is registered.

#### **For Individual,**

- **ie-doc-type (Document Type)**  
This is the type of identification document provided by the registrant as an individual to register this domain. The available options are:
  - Ireland National ID
  - Ireland Driver License
  - Ireland Passport
- **ie-doc-number (Document Number)**  
This is the document number provided by the registrant as an individual to register this domain based on the document type given above.

Submit the request using the following syntax:

Parameter	Obligation	Description	Value
<b>For Company, the parameters below required:</b>			
ie-reg-cof	Required	The country name of company formation. Format in 2-letter country code	TEXT
ie-doc-number	Required	Company registration number	TEXT
<b>For Trademark, the parameters below required:</b>			
ie-reg-name	Required	Registered trademark name	TEXT
ie-doc-number	Required	Registered trademark number	TEXT
ie-doc-origin	Required	The country name where the trademark is registered	TEXT
<b>For Individual, the parameters below required:</b>			
ie-doc-type	Required	The type of identification document provided by an individual as the registrant. Values are mentioned above.	TEXT
ie-doc-number	Required	The document number based on the document type given above.	TEXT

### Example

1. The following request is to add a domain “reseller.ie” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.ie&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&ie-reg-cof=IE&ie-doc-number=43892570213
```

## ▪ **.RO Domain Registration**

### **Restrictions**

Company or Individual anywhere in the world can register .ro domain.

### **Special Input Parameters**

To register .ro, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **ro-local-presence (Instra Local Presence Service)**

This is our local presence service to register .ro domain.

If you set the value of “ro-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Europe to register .ro domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .ro domain:

### **For Company,**

#### ➤ **ro-doc-number (Company Registration Certificate Number)**

Provide company registration certificate number, if company is registered and located outside of Europe.

#### ➤ **ro-fiscal-number (Fiscal Code)**

Provide fiscal code, if company is registered and located in Europe. Otherwise, it is not required.

### **For Individual,**

#### ➤ **ro-doc-number (Identification Number)**

This is the document number of the registrant’s identification such as National ID.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
<b>For Company, if ro-local-presence is set to 0 then parameters below required:</b>			
ro-doc-number	Required	Company registration certificate number for registrant that is located outside of Europe	TEXT
ro-fiscal-number	Optional	Fiscal code for registrant that is located in Europe	TEXT
<b>For Individual, if ro-local-presence is set to 0 then parameters below required:</b>			
ro-doc-number	Required	Registrant’s identification	TEXT

		number such as National ID.	
--	--	-----------------------------	--

### Example

1. The following request is to add a domain “reseller.ro” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.ro&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&ro-local-presence=1
```

2. The following request is to add a domain “reseller.ro” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.ro&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&ro-local-presence=0&ro-doc-number=938571971331
```



## ▪ **.COM.TR Domain Registration**

### **Note:**

Instra local presence service is not available for .com.tr domain.

### **Restrictions**

1. Only company registered in Turkey and anywhere in the world can register .com.tr domain.
2. Company outside of Turkey must provide proof of document stating the business connection with Turkey such as invoice “to” or “from” Turkey via email or fax.

### **Special Input Parameters**

To register .com.tr, the corresponding special information is required to complete the domain registration:

#### ➤ **comtr-reg-type (Company Type)**

This is the type of company whether it is a local Turkish company or company registered outside of Turkey. The available options are:

Turkey Local Company  
Foreign Company

#### ➤ **comtr-doc-type (Document Type)**

This is the type of document provided by the registrant as a company depends on the company type selected. The available options are:

Turkey Company Tax Number (If Turkey Local Company is selected)  
Company Registration Certificate (if the Foreign Company is selected)

#### ➤ **comtr-doc-number (Document Number)**

This is the document number based on the document type provided above.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
comtr-reg-type	Required	Type of the company registered whether it is a Turkey Local Company or Foreign Company	TEXT
comtr-doc-type	Required	Document type must be provided based on the company type selected, values are: “Turkey Company Tax Number” or “Company Registration Certificate”	TEXT
comtr-doc-number	Required	Document number based on the document type must be provided.	TEXT

**Example**

1. The following request is to add a domain “reseller.com.tr” with NO local presence:  
BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.tr&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&comtr-reg-type=Foregin Company&comtr-doc-type=Company Registration Certificate&comtr-doc-number=9381751981311

## ▪ **.LV Domain Registration**

### **Restrictions**

Only individual or company located in Latvia can register .lv domain.

### **Special Input Parameters**

To register .lv domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **lv-local-presence (Instra Local Presence Service)**

This is our local presence service to register .lv domain.

If you set the value of “lv-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Latvia to register .lv domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .lv domain:

### **For Company,**

#### ➤ **lv-doc-number (Document Number)**

This is the Latvian VAT number of the company as the registrant.

### **For Individual,**

#### ➤ **lv-doc-number (Document Number)**

This is the Latvian National ID number of the individual as the registrant.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
lv-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)
<b>For a Company, if lv-local-presence is set to 0 then details below required:</b>			
lv-doc-number	Required	Companies located in Latvia must enter their Latvian VAT number	TEXT
<b>For an Individual, if lv-local-presence is set to 0 then details below required:</b>			
lv-doc-number	Required	Individual located in Latvia must provide their Latvian national ID number	TEXT

### Example

1. The following request is to add a domain “reseller.lv” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.lv&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&lv-local-presence=1
```

2. The following request is to add a domain “reseller.lv” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.lv&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&lv-local-presence=0&lv-doc-number=LV9347112
```

## ▪ **.KR Domain Registration**

### **Restrictions**

Only company registered in Korea or individual located in Korea can register .kr domain.

### **Special Input Parameters**

To register .kr domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **kr-local-presence (Instra Local Presence Service)**

This is our local presence service to register .kr domain.

If you set the value of “kr-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Korea to register .kr domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .kr domain:

### **For Company,**

#### ➤ **kr-doc-type (Certificate Type)**

This is the certificate type of the company as the registrant. The available options are:

- Company Registration Certificate
- Brand Name Registration Certificate
- Service Name Registration Certificate
- School Foundation Certificate

#### ➤ **kr-doc-number (Certificate Number)**

This is the document number based on the document type provided from above.

### **For Individual,**

#### ➤ **kr-doc-type (Certificate Type)**

This is the certificate type of the individual as the registrant. The available options are:

- Passport
- Social Security
- Driver License

#### ➤ **kr-doc-number (Certificate Number)**

This is the certificate number based on the document type provided from above.

Submit the request using the following syntax:

Parameter	Obligation	Description	Value
kr-local-presence	Required	Value is '0' or '1'. Set this parameter to "1", if you require us to provide a local presence in registering the domain.	TEXT ('0'   '1')
<b>For a Company, if kr-local-presence is set to 0 then details below required:</b>			
kr-doc-type	Required	Certificate type of the company as registrant with value mentioned above	TEXT
kr-doc-number	Required	Companies located in Korea must enter their certificate number based on certificate type given	TEXT
<b>For an Individual, if kr-local-presence is set to 0 then details below required:</b>			
kr-doc-type	Required	Certificate type of the individual as registrant with value mentioned above	TEXT
kr-doc-number	Required	Individual located in Korea must provide their certificate number based on certificate type given	TEXT

### Example

1. The following request is to add a domain "reseller.kr" with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.kr&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&kr-local-presence=1
```

2. The following request is to add a domain "reseller.kr" with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.kr&period=1&registrantContact=INS-C-72&adminContact=INS-C-72&techContact=INS-C-72&billingContact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&kr-local-presence=0&kr-doc-type=Social Security&kr-doc-number=943857AB2
```

## ▪ **.COM.PA Domain Registration**

### **Restrictions**

No restriction. Anyone can register .com.pa domain. However, there are special input parameters are required.

### **Special Input Parameters**

To register .com.pa domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **compa-local-presence (Instra Local Presence Service)**

This is our local presence service to register .com.pa domain.

If you set the value of “compa-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will be your agent to register .com.pa domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .com.pa domain:

#### ➤ **compa-doc-type (Document Type)**

This is the document type provided by the registrant. The available options are:

- Company ID
- National ID
- Driver License
- Passport

#### ➤ **compa-doc-number (Document Number)**

This is the document number based on the document type provided from above.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
compa-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)
<b>If compa-local-presence is set to 0 then details below required:</b>			
compa-doc-type	Required	This is the document type with value mentioned above	TEXT
compa-doc-number	Required	This is the document number based on document type given	TEXT

### Example

1. The following request is to add a domain “reseller.com.pa” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.pa&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&compa-local-presence=1
```

2. The following request is to add a domain “reseller.com.pa” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.pa&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&compa-local-presence=0&compa-doc-type=Company ID&compa-doc-number=PA239802148
```



## ▪ **.CO.CR Domain Registration**

### **Restrictions**

No restriction. Anyone can register .co.cr domain. However, there are special input parameters are required.

### **Special Input Parameters**

To register .co.cr domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **cocr-local-presence (Instra Local Presence Service)**

This is our local presence service to register .co.cr domain.

If you set the value of “cocr-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will be your agent to register .co.cr domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .co.cr domain:

#### ➤ **cocr-doc-type (Document Type)**

This is the document type provided by the registrant. The available options are:

- Company ID
- National ID
- Driver License
- Passport

#### ➤ **cocr-doc-number (Document Number)**

This is the document number based on the document type provided from above.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
cocr-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)
<b>If cocr-local-presence is set to 0 then details below required:</b>			
cocr-doc-type	Required	This is the document type with value mentioned above	TEXT
cocr-doc-number	Required	This is the document number based on document type given	TEXT

### Example

1. The following request is to add a domain “reseller.co.cr” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.co.cr  
&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-  
81&billingContact=INS-C-  
81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&cocr-local-  
presence=1
```

2. The following request is to add a domain “reseller.co.cr” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.co.cr  
&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-  
72&billingcontact=INS-C-  
72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&cocr-local-  
presence=0&cocr-doc-type=Company ID&cocr-doc-number=CR239802148
```

## ▪ **.PE Domain Registration**

### **Note:**

- 1) This condition below also applies to **.COM.PE** domain registration as well.
- 2) All prefix “pe” for the special parameters is replace with “compe”.

### **Restrictions**

No restriction. Anyone can register .pe domain. However, there are special input parameters are required.

### **Special Input Parameters**

To register .pe domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **pe-local-presence (Instra Local Presence Service)**

This is our local presence service to register .pe domain.

If you set the value of “pe-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will be your agent to register .pe domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .pe domain:

#### ➤ **pe-doc-type (Document Type)**

This is the document type provided by the registrant. The available options are:

- Company ID
- National ID
- Taxpayer Code
- Driver License
- Passport

#### ➤ **pe-doc-number (Document Number)**

This is the document number based on the document type provided from above.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
pe-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)
<b>If pe-local-presence is set to 0 then details below required:</b>			

pe-doc-type	Required	This is the document type with value mentioned above	TEXT
pe-doc-number	Required	This is the document number based on document type given	TEXT

### Example

1. The following request is to add a domain “reseller.pe” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.pe&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&pe-local-presence=1
```

2. The following request is to add a domain “reseller.pe” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.pe&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&pe-local-presence=0&pe-doc-type=Company ID&pe-doc-number=PE239802148
```

## ▪ **.EC Domain Registration**

### **Note:**

- 1) This condition below also applies to **.COM.EC** and **.INFO.EC** domain registration as well.
- 2) All prefix “ec” for the special parameters is replace with “comec” or “infoec” depends on the domain name being registered.

### **Restrictions**

No restriction. Anyone can register .ec domain. However, there are special input parameters are required.

### **Special Input Parameters**

To register .ec domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **ec-local-presence (Instra Local Presence Service)**

This is our local presence service to register .ec domain.

If you set the value of “ec-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will be your agent to register .ec domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .ec domain:

#### ➤ **ec-doc-type (Document Type)**

This is the document type provided by the registrant. The available options are:

- Company ID
- National ID
- Driver License
- Passport

#### ➤ **ec-doc-number (Document Number)**

This is the document number based on the document type provided from above.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
ec-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)

**If ec-local-presence is set to 0 then details below required:**

ec-doc-type	Required	This is the document type with value mentioned above	TEXT
ec-doc-number	Required	This is the document number based on document type given	TEXT

**Example**

1. The following request is to add a domain “reseller.ec” with local presence:

BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.ec&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&ec-local-presence=1

2. The following request is to add a domain “reseller.ec” with NO local presence:

BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.ec&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&ec-local-presence=0&ec-doc-type=Company ID&ec-doc-number=EC239802148

## ▪ **.COM.AR Domain Registration**

### **Restrictions**

Only company registered in Argentina can register .com.ar domain.

### **Special Input Parameters**

To register .com.ar domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **comar-local-presence (Instra Local Presence Service)**

This is our local presence service to register .com.ar domain.

If you set the value of “comar-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Argentina to register .com.ar domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .com.ar domain:

#### ➤ **comar-doc-number (Document Number)**

This is the company registration certificate number.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
comar-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)
<b>If comar-local-presence is set to 0 then details below required:</b>			
comar-doc-number	Required	Companies located in Argentina must enter their company registration certificate number	TEXT

### **Example**

1. The following request is to add a domain “reseller.com.ar” with local presence:  
 BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.ar&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&comar-local-presence=1

2. The following request is to add a domain “reseller.com.ar” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.  
ar&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-  
72&billingcontact=INS-C-  
72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&comar-local-  
presence=0&comar-doc-number=AR9348722
```



## ▪ **.COM.BR Domain Registration**

### **Restrictions**

Only company registered in Brazil can register .com.br domain.

### **Special Input Parameters**

To register .com.br domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **combr-local-presence (Instra Local Presence Service)**

This is our local presence service to register .com.br domain.

If you set the value of “combr-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Brazil to register .com.br domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .com.br domain:

#### ➤ **combr-doc-number (Company Certificate Number)**

This is the company registration certificate number.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
combr-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)
<b>If combr-local-presence is set to 0 then details below required:</b>			
combr-doc-number	Required	Companies located in Brazil must enter their company registration certificate number	TEXT

### **Example**

1. The following request is to add a domain “reseller.com.br” with local presence:  
 BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.br&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&combr-local-presence=1

2. The following request is to add a domain “reseller.com.br” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.br&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&combr-local-presence=0&combr-doc-number=BR23813552
```

## ▪ **.COM.MY Domain Registration**

### **Restrictions**

1. Only available for a company registered and located in Malaysia.
2. Fixed registration of 1 year

### **Special Input Parameters**

To register .com.my domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **commy-local-presence (Instra Local Presence Service)**

This is our local presence service to register .com.my domain.

If you set the value of “commy-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will be your agent to register .com.my domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .com.my domain:

#### ➤ **commy-doc-type (Company Certificate Type)**

This is the company registration certificate type. The available options are:

- Audit Firm
- Farmers Organisation
- Parent Teachers Association
- Sports Organisation
- Trustee
- Others

#### ➤ **commy-doc-number (Company Certificate Number)**

This is the certificate number based on the certificate type provided from above.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
commy-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)
<b>If commy-local-presence is set to 0 then details below required:</b>			
commy-doc-type	Required	This is the company certificate type with value mentioned above	TEXT

commy-doc-number	Required	This is the company certificate number based on the certificate type given	TEXT
------------------	----------	--	------

### Example

1. The following request is to add a domain “reseller.com.my” with local presence:  
 BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.my&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&commy-local-presence=1

2. The following request is to add a domain “reseller.com.my” with NO local presence:  
 BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.com.my&period=1&registrantContact=INS-C-72&adminContact=INS-C-72&techContact=INS-C-72&billingContact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&commy-local-presence=0&commy-doc-type=Others&commy-doc-number=MY0984284218

## ▪ **.CA Domain Registration**

### **Restrictions**

For registrant of the domain is residing in Canada, registrant legal type **MUST** be provided.

### **Special Input Parameters**

To register .ca domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **ca-local-presence (Instra Local Presence Service)**

This is our local presence service to register .ca domain.

If you set the value of “ca-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will be your agent to register .ca domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .ca domain:

#### ➤ **ca-reg-type (Registrant Legal Type)**

This is the registrant legal type for the registrant is residing in Canada. The accepted value for this parameter is below with each code represents a type of registrant. The available values are:

- CCT = Canadian Citizen
- PRT = Partnership Registered in Canada
- CCO = Canadian Corporation
- RES = Permanent Resident of Canada
- PLT = Canadian Political Party
- ASS = Canadian Unincorporated Association
- ABO = Aboriginal People Indigenous to Canada
- INB = Indian Band of Canada
- GOV = Government in Canada
- EDU = Canadian Educational Institution
- HOP = Canadian Hospital
- LAM = Canadian Library, Archive or Museum
- LGR = Legal Representative of Canadian Citizen
- MAJ = Her Majesty the Queen
- TDM = Trademark Registered in Canada
- OMK = Person Protected by Trademarks Act
- TRD = Canadian Trade Union
- TRS = Trust Established in Canada

Submit the request using the following syntax:

Parameter	Obligation	Description	Value
ca-local-presence	Required	Value is '0' or '1'. Set this parameter to "1", if you require us to provide a local presence in registering the domain.	TEXT ('0'   '1')
<b>If ca-local-presence is set to 0 then details below required:</b>			
ca-reg-type	Required	This is the company certificate type with value mentioned above	TEXT

### Example

1. The following request is to add a domain "reseller.ca" with local presence:  
BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.ca&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&ca-local-presence=1
2. The following request is to add a domain "reseller.ca" with NO local presence:  
BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.ca&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&ca-local-presence=0&ca-reg-type=Canadian Citizen

## ▪ **.DK Domain Registration**

### **Restrictions**

1. Only available to registrant located in Europe countries.
2. Fixed registration of 1, 2, 3 or 5 years.

### **Special Input Parameters**

To register .dk domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **dk-local-presence (Instra Local Presence Service)**

This is our local presence service to register .dk domain.

If you set the value of “dk-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will be your agent to register .dk domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .dk domain:

### **For Company and Individual,**

#### ➤ **dk-doc-number (VAT Number)**

This is the company or individual VAT number.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
dk-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)
<b>If dk-local-presence is set to 0 then details below required:</b>			
dk-doc-number	Required	This is the company or individual VAT number	TEXT

### **Example**

1. The following request is to add a domain “reseller.dk” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.dk&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&dk-local-presence=1
```

2. The following request is to add a domain “reseller.dk” with NO local presence:  
BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.dk&p  
eriod=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-  
72&billingcontact=INS-C-  
72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&dk-local-  
presence=0&dk-doc-number=DK329482048



## ▪ **.FI Domain Registration**

### **Restrictions**

1. Only available for company registered in Finland or individual located in Finland.
2. Fixed registration of 1 year or 3 years.

### **Special Input Parameters**

To register .fi, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **fi-local-presence (Instra Local Presence Service)**

This is our local presence service to register .fi domain.

If you set the value of “fi-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Finland to register .fi domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .fi domain:

### **For Company or Individual,**

#### ➤ **fi-holder-companytype**

This is the type of Finnish company required to register .fi domain. This parameter is optional for registrant type individual.

#### ➤ **fi-doc-number (Document Number)**

This is the document number based on the document type provided from above.

#### ➤ **fi-baseon-personname**

This is the full name of registrant who is located in Finland.

#### ➤ **fi-personname-regid**

This is the type of registration ID of the registrant located in Finland.

#### ➤ **fi-personname-regnumber**

This is the registration ID number of the registrant located in Finland.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
fi-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local	INTEGER (‘0’   ‘1’)

		presence in registering the domain.	
<b>For Company/Individual, if fi-local-presence is set to 0 then parameters below required:</b>			
fi-holder-companytype	Optional	This is the Finnish company type of the registrant	TEXT
fi-doc-number	Required	Document number based on the document type must be provided.	TEXT
fi-baseon-personname	Required	This is the full name of registrant who is located in Finland.	TEXT
fi-personname-regid	Required	This is the type of registration ID of the registrant located in Finland.	TEXT
fi-personname-regnumber	Required	This is the registration ID number of the registrant located in Finland.	TEXT

### Example

1. The following request is to add a domain “reseller.fi” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.fi&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&fi-local-presence=1
```

2. The following request is to add a domain “reseller.fi” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.fi&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&fi-local-presence=0&fi-holder-companytype=Finnish Local Company&fi-doc-number=893759328&fi-baseon-personname=John Resell&fi-personname-regid=Finnish National ID&fi-personname-regnumber=9590422
```

## ▪ **.FR Domain Registration**

### **Restrictions**

1. Only available for a company registred in France or an individual located in France.
2. Fixed registration 1 year.

### **Special Input Parameters**

To register .fr domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **fr-local-presence (Instra Local Presence Service)**

This is our local presence service to register .fr domain.

If you set the value of “fr-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in France to register .fr domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .fr domain:

#### **For Company,**

##### ➤ **fr-doc-number (Document Number)**

This is the SIREN or SIRET number of a company.

#### **For Individual,**

##### ➤ **fr-birth-date (Date of Birth)**

This is the date of birth of the registrant as individual.

##### ➤ **fr-birth-city (City of Birth)**

This is the city of birth of the registrant as individual.

##### ➤ **fr-birth-country (Country of Birth)**

This is the country of birth of the registrant as individual.

##### ➤ **fr-birth-postcode (Postcode)**

This is the postcode of the city of birth of the registrant as individual.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
fr-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the	TEXT (‘0’   ‘1’)

		domain.	
<b>For a Company, if fr-local-presence is set to 0 then details below required:</b>			
fr-doc-number	Required	Companies located in France must provide SIREN or SIRET number	TEXT
<b>For an Individual, if localpresence is set to 0 then details below required:</b>			
fr-birth-date	Required	Individual located in France must provide registrant's date of birth	TEXT
fr-birth-city	Required	Individual located in France must provide registrant's city of birth	TEXT
fr-birth-country	Required	Individual located in France must provide registrant's country of birth	TEXT
fr-birth-postcode	Required	Individual located in France must provide registrant's postcode of the city of birth	TEXT

### Example

1. The following request is to add a domain "reseller.fr" with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.fr&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&fr-local-presence=1
```

2. The following request is to add a domain "reseller.fr" with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.fr&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&fr-local-presence=0&fr-doc-number=49827204244
```

## ▪ **.NO Domain Registration**

### Restrictions

1. Only available for a company registered in Norway.
2. Fixed registration 1 year.

### Special Input Parameters

To register .no domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **no-local-presence (Instra Local Presence Service)**

This is our local presence service to register .no domain.

If you set the value of “no-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Norway to register .no domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .no domain:

#### ➤ **no-org-number (Registered Company Number)**

This is the company/organisation registration number.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
no-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)
<b>If no-local-presence is set to 0 then details below required:</b>			
no-org-number	Required	Companies registered in Norway must provide company registration number	TEXT

### Example

1. The following request is to add a domain “reseller.no” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.no&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&no-local-presence=1
```

2. The following request is to add a domain “reseller.no” with NO local presence:  
BASE\_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.no&  
period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-  
72&billingcontact=INS-C-  
72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&no-local-  
presence=0&no-doc-number=NO391759817301

## ▪ **.RU Domain Registration**

### **Restrictions**

1. Only available for a company registered in Russia and an individual located in Russia.
2. Fixed registration 1 year.

### **Special Input Parameters**

To register .ru domain, the corresponding special information is required to complete the domain registration or otherwise use our local presence service.

#### ➤ **ru-local-presence (Instra Local Presence Service)**

This is our local presence service to register .ru domain.

If you set the value of “ru-local-presence” parameter equal to:

##### ◆ **1 = Use Instra Local Presence, means:**

1. Instra will provide an agent to act for your local presence in Russia to register .ru domain
2. Other special parameters are not required, and
3. The admin contact used for this domain will be Instra agent’s detail

##### ◆ **Otherwise, 0 = Use Registrant Detail, means:**

You are choosing to use your own detail and required to provide the special parameters below to register .ru domain:

### **For Company,**

#### ➤ **ru-doc-number (Document Number)**

This is the taxpayer ID number of the company.

#### ➤ **ru-territory-number (Territory-Linked Number)**

This is the territory-linked number of the company.

### **For Individual,**

#### ➤ **ru-doc-number (Passport Number)**

This is the registrant’s passport number.

#### ➤ **ru-dob (Date of Birth)**

This is the registrant’s date of birth.

**Submit the request using the following syntax:**

Parameter	Obligation	Description	Value
ru-local-presence	Required	Value is ‘0’ or ‘1’. Set this parameter to “1”, if you require us to provide a local presence in registering the domain.	TEXT (‘0’   ‘1’)
<b>For Company, if ru-local-presence is set to 0 then details below required:</b>			
ru-doc-number	Required	Companies registered in	TEXT

		Russia must provide taxpayer id of the company	
ru-territory-number	Required	Companies registered in Russia must provide the territory-linked number	TEXT
<b>For Individual, if ru-local-presence is set to 0 then details below required:</b>			
ru-doc-number	Required	Passport number of an individual as the registrant	TEXT
ru-dob	Required	The date of birth of an individual as the registrant	TEXT

### Example

1. The following request is to add a domain “reseller.ru” with local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.ru&period=1&registrantContact=INS-C-72&adminContact=INS-C-81&techContact=INS-C-81&billingContact=INS-C-81&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&ru-local-presence=1
```

2. The following request is to add a domain “reseller.ru” with NO local presence:

```
BASE_URL?user=reseller.com&pw=secret&command=CreateDomain&domain=reseller.ru&period=1&registrantcontact=INS-C-72&admincontact=INS-C-72&techcontact=INS-C-72&billingcontact=INS-C-72&nameserver1=ns1.resellerdns.com&nameserver2=ns2.resellerdns.com&ru-local-presence=0&ru-doc-number=1937330&ru-territory-number=RU349981
```